

# VITRABLOK, s. r. o.

---

## DECLARATION OF PERFORMANCE

**Declaration number:** 49/Q30Doric/1/16

**1. Unique identification code of the product-type:**

Welded glass block

**2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):**

Q30 Doric

**3. Intended use or uses of the construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:**

Use for building of non-bearing constructions.

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):**

Vitrablok, s. r. o.  
Bílinská 42  
Duchcov  
419 14  
Czech Republic

**5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):**

Petr Králík  
Plant manager  
Vitrablok, s. r. o.  
Bílinská 42  
Duchcov  
419 14  
Czech Republic

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

System 4

**7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:**

According to European commission for construction products No. 305/2011, Vitrablok, s. r. o. declares that the construction product is in conformity with standard stated by harmonized norm EN 1051-1:2003. The construction product is safe when used as stated in point 3.

The evaluation of conformity was performed according to EN 1051-2.

## 8. Declared performance:


<i>Essential characteristic</i>	<i>Performance</i>	<i>Harmonized technical specification</i>
Reaction on fire	Euroclass A1	EN 13501-1
Bullet resistance	NPD	EN 1063
Explosion resistance	NPD	EN 13541
Burglar resistance	NPD	EN 356
Resistance to temperature differences	30 K	EN 1051-2
Mechanical resistance (compressive strength)	> 8 MPa	EN 1051-1
Sound insulation	40 dB	EN 140-3 EN 717-1
Thermal insulation (U)	2.9 Wm <sup>-2</sup> K <sup>-1</sup>	EN 673
Light transmission: clear sandblasted (one side) sandblasted (both sides)	79% NPD NPD	EN 410
Solar energy characteristics (g): clear sandblasted (one side) * sandblasted (both sides)	75% NPD NPD	EN 410

\* First value is determined for radiation incidence onto non-sandblasted surface, second onto sandblasted one.

## 9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8:

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

  
.....  
Petr Králík  
Plant manager

Duchcov (Czech Republic), 8<sup>th</sup> January 2016